

CARBON

3-in-1 room sensor

Nexelec

www.nexelec.fr



Connected

Remote reading of measurements. All information is available in a secure cloud

Monitors indoor air quality



The CO2 sensor analyzes the atmosphere every 5 minutes and informs if it is necessary to ventilate or close the window

Temperature | Humidity

For better indoor comfort. Measures ambient parameters in offices or homes

10-years⁽¹⁾ battery

High-performance lithium battery

Indicator light

The Green / Orange / Red indicator changes in accordance to the CO2 level and alerts you when it's time to ventilate and renew indoor air

Regulatory compliance

Direct-reading sensor compliant with French standards for measuring CO2 concentration in indoor air

Calibration certificate

Accurate CO2, temperature and humidity measurements validated by a COFRAC-accredited metrology laboratory

Accuracy of CO2 measurement

No risk of measurement drift over time. Automatic weekly recalibration of the CO2 sensor. Manual sensor calibration is also possible

 Carbon Dioxide


 Temperature

 Humidity

CARBON

3-in-1 room sensor

Nexelec



Reference	Radio	Frequency
I420LR	LoRaWAN	EU868 MHz
I420SF	Sigfox	EU868 MHz
I420EO	EnOcean	EU868 MHz

FUNCTIONS



Easy to install

Free-standing on a desk or wall-mounted. Adhesive mounting included



Easy to configure

Easy product adjustment via contactless NFC technology from a smartphone



Instantaneous measurement

Easy to operate, thanks to a button on the front of the sensor. Useful for occupants or technicians (function can be deactivated)



Anti-theft protection

Lockable mounting base reduces risk of sensor removal



Design

Facilitates product acceptance by occupants

FEATURES



Carbon Dioxide

Res.: 1 ppm
Prec.: $\pm(30 \text{ ppm} + 3\% \text{ value})$
Measuring range: 0 - 10 000 ppm



Temperature

Res.: 0.1°C
Prec.: $\pm 0.3^\circ\text{C}$
Measuring range: -30°C à $+70^\circ\text{C}$



Humidity

Res.: 0.5% R.H.
Prec.: $\pm 2\% \text{ R.H.}$
Measuring range: 0 - 100% R.H.



Choice of connectivity



Conditions of use

Indoor environment
Temperature: 0°C to $+50^\circ\text{C}$
Hygrometry: 0% RH to 95% RH (non-condensing)

Mounting type

Wall-mounted or free-standing

Warranty⁽²⁾

2 years

Set contents

1 sensor
1 mounting base
1 removable stand
1 AC adapter
1 1.8m USB-C cable
2 nylon screws and plugs
1 3M® adhesive fastener

Certification



⁽¹⁾ Battery life is not guaranteed and may vary according to product settings and use. ⁽²⁾ Please refer to the information available on the www.support.nexelec.fr website.